



NOKIA ONT - PASSIVE OPTICAL LAN

COM. REFERENCE

Develop for Enterprise FX DC

18.03.2019

Data Sheet: 019/052-Com_POL-Sales

GENERAL FEATURES

- ☆ Compliant with ITU-T G.984 and supports a line rate of 2.5 Gb/s downstream and 1.25 Gb/s upstream
- ☆ With GPON as the uplink interface, supports standard triple play services – voice, video and high-speed internet access for home networking
- ☆ Managed from a remote site using Nokia Software Platform Passive Optical LAN Command Center
- ☆ Supports the full range of fault, configuration, accounting, performance and security (FCAPS) functions
- ☆ Supports full triple play services including voice, video and high-speed internet access
- ☆ G.984 compliant
- ☆ Wall, ceiling, desktop mounting or outdoor mounting in a Nokia universal ONT enclosure SUF
- ☆ Optimized for Gigabit services with Nokia Gigabit Express
- ☆ Delivers voice services using voice over IP (VoIP)
- ☆ Supports IP video distribution
- ☆ Delivers video services efficiently with multicasting or unicasting
- ☆ Single fiber network offers flexible support for multiple service and content providers
- ☆ Lowers OPEX through use of a single fiber network
- ☆ 2.488G downstream receiver compliant

COM. REFERENCE

Develop for Enterprise ONT DC

18.03.2019

NOKIA ONT POL TYPE G4 UNIT

The Nokia Intelligent Services Access Manager Optical Network Terminal (ONT) KROG-240G-A is designed to deliver gigabit speeds in an Optical LAN environment. The Nokia ONT KROG-240G-A for Optical LAN provides two voice and four Gigabit Ethernet (GigE) interfaces to the desktop and delivers premium service experience for all services including voice, data and video. This ONT terminates a full standard compliant Gigabit Passive Optical Network (GPON) fiber interface.

The Nokia ONT KROG-240G-A for Optical LAN is designed for businesses, hospitals, hotels, real estate developers and universities to deliver premium service experiences and provide long- term value for your LAN. Voice services are provided through two POTS ports with an integrated analog telephone adapter (ATA) that converts voice traffic into Session Initiation Protocol (SIP) or ITU-T H.248. This ONT is compatible with Nokia OLT POL FX access node and managed through the Nokia Software Platform Passive Optical LAN Command Center (KPCC).



Model	Nr. of	RJ45	Dim.	GPON	WiFi
	Subscribers	Slot	in cm	Interface	
KROG-010G-A	4 + 2 TEL (analog)	4	33mm x 208mm x 142mm	4 x 10/100/1000	NO

Technical Specification

GPON network interface

- Compliant to G.984.x GPON standards
- BSmall form-factor (SFF) type laser, SC/APC connector
- High-speed Internet access
- 1.244G burst mode upstream transmitter
- 2.488G downstream receiver compliant
- Laser compliant to FCC 21 CFR Part 15, Class B

Ethernet

- 4 x 10/100/1000Base-T interface with RJ-45 connectors
- Ethernet port auto negotiation or manual configuration
- Medium dependent interface/medium dependent interface crossover (MDI/MDIX) automatic sense
- Supports port-based downstream priority queues and strict priority scheduling for traffic class of service (CoS) differentiation
- Virtual switch based on 802.1Q VLAN
- VLAN tagging/detagging per Ethernet port and marking/remarking of 802.1p
- Supports any source multicast/source-specific multicast (ASM/SSM)
- SIPv4 type of service/differentiated services code point (ToS/DSCP) to 802.1p mapping for untagged frames

Power supply

- Local powering with 12 V (feed using external AC/DC adapter)
- Dying gasp support
- Power consumption: <8W

Operating Temperature

- 40°C to 60°C (-40°F to 140°F)
- Relative humidity: 5% to 90%

Operations, administration, and maintenance (OAM)

- Standard-compliant OMCI (the embedded operations channel) interface as defined by G.984.4 and G.988

- Supports local web GUI for the optical network unit (ONU) authentication password configuration from the LAN side
- Management information base (MIB) manipulation over OMCI using the create, delete, set, get, and get next commands
- Provisioning of Ethernet service
- Alarm reporting and performance monitoring
- Remote software image download over OMCI, as well as activation and rebooting
- Supports SLID (using POTS port or web GUI)

GPON TC layer

- G.984.3-compliant GPON Encapsulation Method (GEM) framing
- Multiple T-CONTs per device
- Multiple GEM ports per device
- Flexible mapping between GEM ports and T-CONTs
- G.984.3-compliant activation with automatically discovered SN and password
- G.984.3-compliant activation with automatically discovered SN and password
- G.984.3-compliant Advanced Encryption Standard (AES-128)
- G984.3-compliant forward error correction (FEC)

Safety and electromagnetic interference (EMI)

- UL 60950-1
- CSA C22.2 No. 60950-1
- FCC Part 15b, Class B, IC-003
- ITU-T K.21

LED

- Power; - Alarm; -BTRY; - Fail; Data 1-4, - NTKW, MGMT, -POTS

WARRANTY

This product manufactured for Kronect Comunicatii SRL is warranted to be free from defects from workmanship and components for a period of 2 years from the date of shipment. During this period any defective products shipped prepaid to Kronect will be repaired or replaced at our discretion and returned at no further cost to the customer. Kronect shall not be liable for any consequential or indirect damage of any type or nature, nor for any cost of reinstallation. Any product that has been subject to improper installation, unauthorized alteration, accident or misuse is rendered void of warranty.

Kronect also provides a repair service for products not covered by warranty. Charges will be levied for labor, components, and transportation.

To return a unit for repair contact the Kronect and obtain a Return Material Authorization Number (RMA.)

Be prepared to provide the following information:

1. Product Name
2. Product Model Number
3. Product Serial Number (stick on each products)
4. Your contact person and phone number.
5. Your company name and return address

Package the unit in its original shipping carton or adequate substitute, along with a clear & complete description of the problem or defect. Clearly mark the outside of the carton with the Return Material Authorization Number and send the unit to the address shown below:

KRONECT COMUNICATII SRL

Str. 1Decembrie Nr.136, City Tunari, District Ilfov, Romania 077180

Phone: +40(212) 529-718

Fax: +40(212) 529-719

E-mail: comercial@kronect.ro Internet: <http://www.kronect.ro>

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.